

**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 BASE**
**SECTION 1 Identification of the substance**

Trade Name	<b>SIMAZINC EP PRIMER BASE</b>
Product Code	<b>1402-00</b>
Product Type	Solvent based
Manufacturer's data	PT. SIGMA UTAMA Jl. Landbouw No.1 Citeureup – Bogor, INDONESIA + 62-21-87 3042 (Fax)
Emergency Telephone No.	+ 62-21-87 6310 (Office Hours)

**SECTION 2 Hazard identification**

OSHA/HCS Status                      Considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Classification of the substance or mixture                      FLAMMABLE LIQUIDS – Category 3  
 SKIN CORROSION/IRRITATION - Category 2  
 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) – Category 3  
 AQUATIC TOXICITY (CHRONIC) – Category 2

**Label elements**

Hazard pictograms



Signal Word                                      Warning

Hazard Statements                      H226- Flammable liquid and vapor  
 H318- Causes serious eye damage  
 H315- Causes skin irritation  
 H317- May cause an allergic skin reaction  
 H410- Very toxic to aquatic life with long lasting effects

**Precautionary statements**

Prevention                                      Avoid breathing vapors, spray or mists. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep out of reach of children. Keep container tightly closed. Use personal protective equipment as required.

Response                                      IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs : get medical attention

Storage                                      Store in a cool, well-ventilated area Store in a cool, well-ventilated area

Disposal                                      Dispose of contents and container in accordance with all local, regional, national and international regulation

Hazardous ingredients                      Xylene, bisphenol A-epichlorhydrin  
 Other Hazards                                  None Known

**SECTION 3 Composition**

Ingredient	CAS No	Conc. range (%)	GHS Classification
Xylene	1330-20-7	5 - 15	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335

**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 BASE**

			Asp. Tox. 1;H304
Bisphenol A -epichlorohydrin	25068-38-6	20 - 35	Skin Irrit H317 Eye Irrit H318 Asp. Tox. H335 Fertility Dam H360
Oxitol	110-80-5	5-10	-----
Zinc Dust	7440-66-6	20-30	-----

Concentrations shown as range to protect confidentiality or due to batch variation.

**There are no additional ingredients presents which, within the currenet knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and environment and hence require reporting in this section**

**SECTION 4 First Aid Measure**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If breathing is irregular, drowsiness, loss of consciousness or cramps : call 112 and give immediate treatment (first aid)

**Eye contact** Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention.

**Inhalation** Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and get medical attention immediately

**Skin contact** Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners

**Ingestion** If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat

**Protection of first-aider** No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

**SECTION 5 Fire Fighting Measure**

**Extinguishing media** Recommended : Alcohol resistant foam, CO2 ,powder, water spray (foam)  
Not to be used : water jet

**Hazards from the substance or mixture** Flammable liquid and vapor. In a fire or heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.  
This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** Decomposition products may include the following materials : carbon oxides metal oxide/oxides.

**Special equipment for fire fighter** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**SECTION 6 Accidental release measurement**

**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 BASE**
**Personal precautions, protective equipment and emergency procedures**

No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations. Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

**Environmental precautions**

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities

**Methods for cleaning up**

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product.

**SECTION 7 Handling and storage**
**Handling**

Vapor are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used. Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see section 8. Always keep in containers made from the same material as the original one.

**Storage**

Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from : Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

**SECTION 8 Exposure control/personal protection**

Ingredient	Exposure limit
Oxitol	OSHA PEL 200 ppm TWA; 740 mg/m <sup>3</sup> TWA NIOSH 0.5 ppm TWA; 1.8 mg/m <sup>3</sup> TWA 500 ppm IDLH
Xylene	OSHA 2013 TWA : ppm (435 mg/m <sup>3</sup> )

**Personal Protection**


Use a NIOSH APPROVED RESPIRATOR  
Use GOGGLES OR FACE SHIELD

**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 BASE**

RUBBER GLOVES AS NEEDED  
 USE APRON OR OTHER CLOTHING TO AVOID SKIN CONTACT

Personal protective equipment should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Use a properly fitted, air-purifying or air fed respirator complying with an approved standard. Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.

- Engineering controls** Keep gas, vapor, or dust cocentration below any lower explosive limit. Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location
- Hygiene measures** Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.
- Environmental exposure controls** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filter or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels

**SECTION 9 Physical and chemical properties**

Physical	Liquid- Grey
Odor	Solvent-like
Flash point	Closed up ; 12°C
Vapor density	Heavier than air
Spesific density	1.80 ± 0.15 kg /litre
Viscosity	25-30 Poise/Str
Solubilities	Insoluble in water

**SECTION 10 Stability and reactivity**

- Reactivity and chemical stability** **Conditions to avoid** : Avoid temperatures above 60°C (140 F), direct sunlight and contact with sources of heat.  
**Hazardous reactions** : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Hazardous decomposition products** Under norma conditions of storage and use, hazardous decomposiiton products should not be produced
- Conditions to avoid** Avoid all possible sources of ignition (spark or flame). Do not pressurized, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition

**SECTION 11 Toxicological information**

Ingredient	Oral LD 50, mg/kg	Skin LD 50, mg/kg	Inhalation vapor LD 50, mg/l/4 hours
Bisphenol A –epicholorohydrin	4000 mg/kg, rat	20000 rabbit	No data
Xylene	4300 mg/kg, rat	>2000 mg/kg, rabbit	6350 ppm, rat
Oxitol	2125, Rat	3,6, rabbit	2000 ppm, rat

**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 BASE**
**SECTION 12 Ecological information**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	96 hr EC50 algae, mg/l
Oxitol	>10000, Bluegill/sunfish	>10000, Waterflea Daphnia	430, Phytobacterium phosphoreum
Xylene	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
Bisphenol A – epichlorohydrin	9.4, Marinewater fish	21 days: 3.16, Daphnia magna	96 hours: 1.1 Marinewater algae

Environmental precaution : harmful to aquatic organism, may cause long term adverse effect in the aquatic environment.

**SECTION 13 Disposal consideration**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations.

Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

The information presented below only applies to the material as supplied. The identification based on characteristic or listing may not apply if the material has been used or otherwise contaminated.

**SECTION 14 Transport information**

Transport within user's premises	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage
----------------------------------	---

	UN no.	Proper shipping name	Transport hazard class(es)	PG*	Env*	Additional information
ADR/RID Class	UN 1263	Paint	3 -	III	Yes	
IMDG Class	UN1263	Paint	3 -	III	Yes	
IATA Class	UN1263	Paint	3 -	III	Yes	

PG\* : Packing group

Env\* : Environmental hazards

**SECTION 15 Regulatory information**

Safety, health and environmental regulation/legislation specific for the substance or mixture

**SECTION 16 Other information**

Abbreviation and acronyms      GHS = Globally Harmonized System of Classification and Labelling of Chemicals

**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 BASE**

## Disclaimer

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, NEITHER PT. SIGMA UTAMA NOR ANY SUBSIDIARIES ASSUMES ANY LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED IN CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CAN NOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS, WHICH EXIST.

**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 HARDENER**
**SECTION 1 Identification of the substance**

Trade Name	<b>SIMAZINC EP PRIMER HARDENER</b>
Product Code	<b>1402-00</b>
Product Type	Solvent based
Manufacturer's data	PT. SIGMA UTAMA Jl. Landbouw No.1 Citeureup – Bogor, INDONESIA + 62-21-87 3042 (Fax)
Emergency Telephone No.	+ 62-21-87 6310 (Office Hours)

**SECTION 2 Hazard identification**

OSHA/HCS Status	Considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)
Classification of the substance or mixture	FLAMMABLE LIQUIDS – Category 3 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) – Category 3 AQUATIC TOXICITY (CHRONIC) – Category 2

**Label elements**

Hazard pictograms



Signal Word	Warning
Hazard Statements	H226- Flammable liquid and vapor H318- Causes serious eye damage H315- Causes skin irritation H317- May cause an allergic skin reaction H410- Very toxic to aquatic life with long lasting effects

**Precautionary statements**

Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Wash hands thoroughly after handling.
Response	Collect spillage. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get a medical if you feel unwell. IF SWALLOWED: Immediately call a medical center. Do not induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	Store locked up Store in a cool, well-ventilated area Store in a cool, well-ventilated area



**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 HARDENER**

Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulation
Supplemental label elements	Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and receiving equipment. These alone may be insufficient to remove static electricity. Avoid contact with skin and clothing. Wash thoroughly after handling.
Hazards not otherwise classified	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire or explosion. Prolonged or repeated contact may dry skin and cause irritation. Repeated or prolonged overexposure to certain chemicals in this product may exacerbate the hearing loss effects associated with noise exposure.
Hazardous ingredients	Xylene, isobutanol
Other Hazards	None Known

**SECTION 3 Composition**

Ingredient	CAS No	Conc. range (%)	GHS Classification
Xylene	1330-20-7	12-20	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335 Asp. Tox. 1;H304
Polyamide Resin	68082-29-1	25-30	H334Skin Irrit Acute Tox. 4;H312 Skin Irrit. 2;H315 Eye Irrit. 2;H319
Isobutanol	78-83-1	5-10	Flam. Liq. 3;H226 Skin Irrit. 2;H315 EyeDam.1,H318, STOTSE3, H335

Concentrations shown as range to protect confidentiality or due to batch variation.

**There are no additional ingredients presents which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and environment and hence require reporting in this section**

**SECTION 4 First Aid Measure**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If breathing is irregular, drowsiness, loss of consciousness or cramps : call 112 and give immediate treatment (first aid)

<b>Eye contact</b>	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 10 minutes. Seek immediate medical attention.
<b>Inhalation</b>	Remove victim to fresh air, and keep person at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and get medical attention immediately
<b>Skin contact</b>	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners
<b>Ingestion</b>	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.



**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 HARDENER**

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Protection of first-aider**

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

**SECTION 5 Fire Fighting Measure****Extinguishing media**

Recommended : Use caution when applying carbon dioxide in confined spaces.  
SMALL FIRE: Steam, CO<sub>2</sub>, dry chemical or inert gas (e.g., nitrogen).  
LARGE FIRE: Use foam, water fog or water spray. Water fog and spray are effective in cooling containers and adjacent structures. However, water can cause frothing and/or may not extinguish the fire. Water can be used to cool the external walls of vessels to prevent excessive pressure, ignition or explosion.  
Not to be used : water jet

**Hazards from the substance or mixture**

Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products**

Decomposition products may include the following materials : carbon dioxide, carbon monoxide

**Special equipment for fire fighter**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**SECTION 6 Accidental release measurement****Personal precautions, protective equipment and emergency procedures**

No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations. Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

**Environmental precautions**

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities

**Methods for cleaning up**

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product.

**SECTION 7 Handling and storage****Handling**

Vapor are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used. Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored

**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 HARDENER**

and processed. Appropriate personal protective equipment: see section 8. Always keep in containers made from the same material as the original one.

**Storage**

Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from : Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

**SECTION 8 Exposure control/personal protection**

Ingredient	Exposure limit
Xylene	<b>OSHA 2013</b> TWA : 100 ppm 435 mg/m <sup>3</sup>
IBA	<b>OSHA PEL</b> TWA 100 ppm 300 mg/m <sup>3</sup>

**Personal Protection**


Use a NIOSH APPROVED RESPIRATOR  
 Use GOGGLES OR FACE SHIELD  
 RUBBER GLOVES AS NEEDED  
 USE APRON OR OTHER CLOTHING TO AVOID SKIN CONTACT

Personal protective equipment should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Use a properly fitted, air-purifying or air fed respirator complying with an approved standard. Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.

**Engineering controls**

Keep gas, vapor, or dust cocentration below any lower explosive limit. Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location

**Hygiene measures**

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.

**Environmental exposure controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filter or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels

**SECTION 9 Physical and chemical properties**

Physical	Light Yellowish Liquid
Odor	Solvent-like
Flash point	Closed cup ; 100 <sup>o</sup> C
Vapor density	Heavier than air
Spesific density	0.90 ± 0.05 kg /litre
Viscosity	15-25 Second/DIN4
Solubilities	Insoluble in water

**SECTION 10 Stability and reactivity**

**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 HARDENER**

Reactivity and chemical stability	<b>Conditions to avoid</b> : Avoid temperatures above 60°C (140 F), direct sunlight and contact with sources of heat. <b>Hazardous reactions</b> : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced
Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurized, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition

**SECTION 11 Toxicological information**

Ingredient	Oral LD 50, mg/kg	Skin LD 50, mg/kg	Inhalation vapor LD 50, mg/l/4 hours
Polyamide Resin	2500 mg/kg, rat	805 mg/kg, rabbit	No data
Xylene	4300 mg/kg, rat	>2000 mg/kg, rabbit	6350 ppm, rat
Isobutanol	2460 mg/kg rat	No data	No data

**SECTION 12 Ecological information**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	96 hr EC50 algae, mg/l
Polyamide resin	570, Poecilia reticulata	31,1 Daphnia Magna	2,5 Scenedesmus subspicaus
Xylene	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales

Environmental precaution : harmful to aquatic organism, may cause long term adverse effect in the aquatic environment.

**SECTION 13 Disposal consideration**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations.

Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

The information presented below only applies to the material as supplied. The identification based on characteristic or listing may not apply if the material has been used or otherwise contaminated.

**SECTION 14 Transport information**

Transport within user's premises	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage
----------------------------------	---

	UN no.	Proper shipping name	class	Transport hazard class(es)	PG*	Env*	Additional information
ADR/RID Class	UN 1263	Paint	3 -		III	Yes	
IMDG Class	UN1263	Paint	3 -		III	Yes	
IATA Class	UN1263	Paint	3 -		III	Yes	

PG\* : Packing group

Env\* : Environmental hazards

**SAFETY DATA SHEET**

Date of issue : September 2021

**SIMAZINC EP PRIMER 1402-00 HARDENER**

---

**SECTION 15 Regulatory information**

Safety, health and environmental regulation/legislation specific for the substance or mixture

**SECTION 16 Other information**Abbreviation and  
acronymsGHS = Globally Harmonized System of Classification and Labelling of  
Chemicals

Disclaimer

**TO THE BEST OUR KNOWLEDGE, THE INFORMATION CONTAINED HERE IN IS ACCURATE. HOWEVER, NEITHER PT. SIGMA UTAMA NOR ANY SUBSIDIARIES ASSUMES ANY LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIAL MAY PRESENT UNKNOWN HAZARD AND SHOULD BE USED IN CAUTION. ALTHOUGH CERTAIN HAZARD ARE DESCRIBED HEREIN, WE CAN NOT GUARANTEE THAT THESE ARE THE ONLY HAZARD, WHICH EXIST.**